



Baldan

TILLAGE EQUIPMENT



TILLAGE EQUIPMENT

OFFSET DISC HARROW

Specifications	CRSG 18	CRSG 20	CRSG 24	CRI 24	CRI 28	CRI 32	CRI 36	CRI 40	CRI 44	CRI A48
No of Discs	18	20	24	24	28	32	36	40	44	48
Disc Diameter (mm)	26"x7.5	26"x7.5	26"x7.5	26"x7.5	26"x7.5	28"x7.5	28"x7.5	28"x7.5	28"x7.5	28"x7.5
Axle Diameter (inch)	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8	1.5/8
Approx. Working Width (m)	2	2.25	2.7	3.1	3.65	4.2	4.7	5.25	5.8	6.2
Working Depth (cm)	150-180	150-180	150-180	150-180	150-180	150-250	150-250	150-250	150-250	150-250
Approx Weight (kg)	1796	1853	1985	2562	2858	3958	4169	4810	5077	6100
Hp required	75	80	100	120	140	160	180	200	220	250

TANDEM DISC HARROWS

Specifications	GCRDALA 60	GCRTI 62	GCRTI 70	GCRTI 78
No of Discs	60	62	70	78
Disc Diameter (mm)	26"x7.5	28"x7.5	28"x7.5	28"x7.5
Axle Diameter (inch)	1.5/8	1.5/8	1.5/8	1.5/8
Approx. Working Width (m)	6.95	8.5	9.6	10.5
Working Depth (cm)	150-180	150-250	150-250	150-250
Approx Weight (kg)	4140	7500	8000	9000
Hp required	240	310	350	390

SUBSOILER

Specifications	ASDA 5	ASDA 7	ASDA 9	ASDA 11	ASDA 13
No of tines	5	7	9	11	13
Tine Spacing	375	375	375	375	375
Cutting Coulter Diameter (inch)	18"	18"	18"	18"	18"
Working Depth (cm)	450	450	450	450	450
Working Width (m)	1875	2625	3375	4125	4875
Approx Weight (kg)	1850	2590	2900	3800	4300
Hp Required	100	140	180	220	260

RIDGER

Specifications	TACR 16
No of discs	16
Disc Diameter (mm)	26"x 6mm
Disc Spacing (mm)	400
Terrace width & Height (mm)	6100x900
Approx Weight (kg)	2410
Hp required	120

POST HOLE DIGGER

Specifications	PSH 9	PSH 12	PSH 18
Auger Diameter (inch)	9"	12"	18"
Hole Depth (mm)	1000	1000	1000
Hole Diameter (mm)	230	310	460
Approx Weight (kg)	164	172	187
Minimum Auger rpm	128	128	128
Hp Required	40	40	40